

ISO 9001-2000 ISO: 14001-1996 OHSAS: 18001-1999

of the work.

नॉर्थ ईस्ट्रर्न इलैक्ट्रिक पावर कॉरपोरेशन लिमिटेड मध्य सम्बद्धाः

NORTH EASTERN ELECTRIC POWER CORPORATION LIMITED (A Government of India Enterprise)

AGTCCPP

RAMCHANDRANAGAR:AGARTALA: TRIPURA (W):PIN-799008:PH. 0381-2391039

NOTICE INVITING TENDER No.34/NEEPCO/AGTCCPP/SRMC/2015-2016, dated -19-02-2016

Sealed tenders in prescribed tender forms under single bid system with 120 (one hundred and twenty) days validity are invited from experienced contractors for the following work:

		<u>*</u>
1.	Name of Work	: Roof treatment of Hospital building AGTCCPP(1st half
2.	Estimated value	portion comprising sitting room of doctor).
2.	Estimated value	:₹218326/- (Rupees two lacs eighteen thousand three hundred twenty six) only.
3.	Earnest Money	: ₹ 4400/- (Rupees four thousand four hundred)
	<u>J</u>	only in the form of Bank Demand Draft issued in
		favour of AGTP,NEEPCO Ltd.
4.	Time of completion	: 45 (forty five) days from the date of issue of Work
		Order.
5.	Tender Document Fee	:₹ 200/- (Rupees two hundred) only in the form of
		Demand Draft/I.P.O. issued in favour of AGTP,
		NEEPCO Ltd.
6.	Sale of Tender Document	:With effect from 20-02-2016 except on holidays
		During 1000 to 1600 Hours from the Office of the
7.	TPA TANK	undersigned.
/-	Time and Date of submission	: Up to 1300 Hours (IST) of 11-03-2016 at the
8.	of Tender	Office of the undersigned.
0.	Time and Date of opening of Tender	: At 1500 Hours (IST) of 11-03-2016 at the Office
	or render	of the undersigned in presence of the bidders or
. 9.	Qualification & Experience	their authorised representatives, if any.
	Quantitation & Experience	: A. The applicant must have successfully completed
		similar nature of work during last 7(seven) years.
		B. Copy of Income Tax PAN and Professional Tax
		Certificate clearance of current validity are to be submitted along with the application.
	Application requesting for purch	ase of tender documents should invariably accompany the
docum	entary evidence satisfying the condit	tion as listed at SI. 9- A & B above and requisite fee for tender
docum	ents.	above and requisite fee for lender
10. Sp	ecial Condition:	
	The intending bidders are requested	to visit the worksite to assess the requirement of the work before
submis	sion of their tenders. The bidder will	have to arrange authorized applicator for carrying out the work.
Other	terms and Conditions:	
11.	Bidders shall have to quote the rat	tes in the rate sheet (Bill of Quantities and Schedule of Rates)
	enclosed with the tender papers.	
12.	ixates quoted by the bidders shall be	e inclusive of all taxes and duties etc. and exclusive Service Tax
	as applicable.	
13.	he recovered from the Lill	vork, ½ % (Half percent) of the value of the complete work shall
	be recovered from the bill her week	of delay subject to maximum of 100/ (Ton agrees) - fel 1

be recovered from the bill per week of delay subject to maximum of 10% (Ten percent) of the value

- 14. Contractor shall submit the EPF Registration Number, if already had, otherwise EPF deduction in respect of both employees and employer's contribution will be made from their bill(s) as per existing relevant norms. However, this will not relieve the Contractor from his responsibility.
- 15. Laws. Regulations and Acts pertaining to engagement of Labours, environment protection, Safety etc. shall be applicable.
- 16. 10% (Ten percent) security deposit will be deducted from the bill(s) for due performance of the work and the same shall be released on expiry of Defect Liability period of 24 (twenty four) months from the date of completion. In case, any defect is noticed during the Defect Liability Period, the contractor will have to rectify/correct the same at his cost and risk; else NEEPCO will get the work done at the cost and risk of the Contractor.
- The Contractor shall have to supply all materials and labours etc. required for the work for successful completion of the same in all respect.
- 18. In case, the work is not been carried out the work as per specifications or not to the satisfaction of NEEPCO or the Contractor causes any damage to the work or property of NEEPCO or other damages not mentioned herein, NEEPCO shall have the right to recover any amount as considered suitable from the bill/ Security deposit/ any other amount due to the Contractor in NEEPCO.
- 19. Tenders received by post at the Office of the undersigned within the specified time mentioned above shall be considered for acceptance. NEEPCO shall not be responsible for any delay in reaching the tenders by post or courier service.

NEEPCO reserves the right to issue tender papers and reject any or all the tenders without assigning any reason thereof. The Corporation is also not bound to accept the lowest tender. Issuance of Tender Papers shall not automatically qualify the bidder for the work.

Sr. Manager(C), AGTCCPP

Memo No. NEEPCO/AGTCCPP/SRMC/T-37(Vol-II)/2015-16/1445-1453,

Dated-19-02-2016

Copy to:

- 1) The Head of Project, AGTCCPP, NEEPCO, for favour of information please with reference to the approved vide no 1168, Dt. 18-02-2016, O/o HOP, AGTCCPP, NEEPCO.
- 2) The Dy. General Manager (IT), NEEPCO, Shillong. He is requested kindly to arrange for uploding of the NIT in NEEPCO website. Copy of the NIT is being sent in advance through e-mail addresses hdeb1976@gmail.com, pkdas@neepco.gov.in, dolanchapac@gmail.com.
- 3) The Sr. Manager (E/M), O&M, AGTCCPP, NEEPCO for information please.
- 4) The Sr. Manager (E/M), Store, AGTCCPP, NEEPCO for information please.
- 5) The Manager (Finance), AGTCCPP, NEEPCO Ltd., for information. He is requested to attend or depute his representative to attend opening of the tender on the scheduled time and date as mentioned in the NIT.
- 6) The Manager(C), AGTCCPP, NEEPCO for information please.
- 7) The Dy. Manager (C), Vigilance, AGTCCPP, NEEPCO for information please.
- The Manager(C&P), AGTCCPP, NEEPCO for favour of information please and requesting for uploading at the CPP Portal.
- 9) Notice Board.
- 10) C/S file.

Sr. Manager(C)

RATE SHEET

Name of work :- Roof treatment of Hospital Building of AGTCCPP (1st Half portion comprising sitting room of doctor).

		9. Charges of lif					
Charges of transportation and disposal of rubbish and stacking of usable material at a	a mound level and stack	Charges of lifting stone aggregate by Head Load to the top of building upto a height of 5.50m above the ground level and stacking at a suitable location complete. Charges of lifting APP Sheet by Head Load to the top of building upto a height of 5.50m above the ground level and stacking at a suitable location complete.	Charges of lifting sand by Head Load to the top of building up the ground level and stacking at a suitable location complete. Charges of lifting stone aggregate by Head Load to the top of 5.50m above the ground level and stacking at a suitable loca Charges of lifting APP Sheet by Head Load to the top of build charges of lifting APP Sheet by Head Load to the top of build charges of lifting APP Sheet by Head Load to the top of build charge the ground level and stacking at a suitable location contains the same stacking at the same stacking at the same stacking at a suitable location contains the same stacking at the same stackin	Charges of lifting cement bags by Head Load to the top of building above the ground level and stacking at a suitable location complete charges of lifting sand by Head Load to the top of building upto a high ground level and stacking at a suitable location complete. Charges of lifting stone aggregate by Head Load to the top of building to the complete of building at a suitable location complete. Som above the ground level and stacking at a suitable location complete above the ground level and stacking at a suitable location complete.	Providing and laying grading of roof for per direction of the Engineer-in-charge: (i) Cement concrete 1:2:4 (1 cement: 2 (ii) Cement size). Charges of lifting cement bags by Head above the ground level and stacking at Charges of lifting sand by Head Load to the ground level and stacking at a suital Charges of lifting stand stacking at a suital Charges of lifting stand stacking at a suital Charges of lifting stone aggregate by He G.5:0m above the ground level and stacking at a shape the ground level and stacking at a suital charges of lifting APP Sheet by Head Load stacking at a suital charges of lifting APP Sheet by Head Load stacking at a suital charges of lifting APP Sheet by Head Load shows the ground level and stacking at a suital charges of lifting APP Sheet by Head Load shows the ground level and stacking at a suital charges of lifting APP Sheet by Head Load shows the ground level and stacking at a suital charges of lifting APP Sheet by Head Load shows the ground level and stacking at a suital charges of lifting APP Sheet by Head Load shows the ground level and stacking at a suital charges of lifting APP Sheet by Head Load shows the ground level and stacking at a suital charges of lifting APP Sheet by Head Load shows the ground level and stacking at a suital charges of lifting APP Sheet by Head Load shows the ground level and stacking at a suital charges of lifting APP Sheet by Head Load shows the ground level and stacking at a suital charges of lifting APP Sheet by Head Load shows the ground level and stacking at a suital charges of lifting at a suital shows the ground level and stacking at a suital shows the ground level and stacking at a suital shows the ground level and stacking at a suital shows the ground level and stacking at a suital shows the ground level and stacking at a suital shows the ground level and stacking at a suital shows the ground level and stacking at a suital shows the ground level and stacking at a suital shows the ground level and stacking at a suital shows the ground level and	Half brick masonry with first class bricks in superstructured levels in cement morter 1:4 (1 Cement: 4 Fine sand). 12 mm cement plaster in single layer including cost of movement plaster in single layer including cost of movement morter 1:4 (1 cement: 4 fine sand). Charges of making chases in walls/ floors including makapp sheet as per the specification and direction of the Environding and laying APP (Atactic Polypropylene Polymos) and making chases in walls/ floors including makapp sheet as per the specification and direction of the Environding and laying APP (Atactic Polypropylene Polymos) and matic consisting of a coat of bitumen primer for bitumen in the same membrane manufacture of density at 25 oC, 0 160 cps. over the primer coat the layer of membrane shaseling all joints etc. and preparing the surface complete the virtual physical and chemical parameters of the membrane shaseling all joints etc. and preparing the surface complete. The virtal physical and chemical parameters of the membrane shaseling all joints etc. and preparing the surface complete than 150 oC. Cold flexibility shall be upto -2 oC when test stand property of membrane as per specification and institution of the Engineer-in-charge: (1) Cement concrete 1:2:4 (1 cement: 2 fine sand: 4 granding and laying grading of roof for water proofing the per direction of the Engineer-in-charge: (1) Cement concrete 1:2:4 (1 cement: 2 fine sand: 4 granding size). Providing and laying cement bags by Head Load to the top of building the ground level and stacking at a suitable location complex the ground level and stacking at a suitable location complex the ground level and stacking at a suitable location complex the ground level and stacking at a suitable location complex the ground level and stacking at a suitable location the top of lifting APP. Sheet by Head Load to the top of labove the ground level and stacking at a suitable location complex the ground level and stacking at a suitable location complex the ground level and stacking at a suitable	Charges of removing the damaged bitumen fell disposal of debris at a suitable location having instruction of the Engineer-in-charge complete. Half brick masonry with first class bricks in supy level: In cement mortar 1:4 (1 Cement: 4 Fin 12 mm cement plaster in single layer including even and smooth and curing complete. In Cement mortar 1:4 (1 Cement: 4 Fin 12 mm cement plaster in single layer including even and smooth and curing complete. In Cement mortar 1:4 (1 Cement: 4 Fin 12 mm cement plaster in single layer including even and smooth and curing complete. In Cement to Charges of making chases in walls/ floors including even and smooth and curing complete. In Cement to Charges of making APP (Atactic Polypropylen 3 mm thick water proofing membrane, black fin matt consisting of a coat of bitumen primer for 1 the same membrane manufacture of density at 160 cps. over the primer coat the layer of membrane saling all joints etc. and preparing the surface The vital physical and chemical parameters of thoughtudinal and transverse direction as 300/25/147. The laying of membrane as per specification of the Engineer-in-charge: (14 T. The laying of membrane as per specification complete. S147. The laying of membrane as per specification manufacture of membrane as per specification complete. Charges of lifting cement bags by Head Load to the top the ground level and stacking at a suitable local Charges of lifting sand by Head Load to the showe the ground level and stacking at a suitable above the ground level and stacking at a suitable local Charges of lifting APP Sheet by Head Load to the showe the ground level and stacking at a suitable local control of the provided level and stacking at a suitable local control of the sui
above the ground level and stacking at a suitable location complete Charges of transportation and disposal of rubbish and stacking of us	the same and the same same	egate by Head Load to the land stacking at a suita	ad Load to the top of bug at a suitable location og at a suitable location og at a suitable and stacking at a suitable hy Head Load to the tor	gs by Head Load to the tatacking at a suitable located and Load to the top of but and Load to the together by Head Load to the together toge	of roof for water proofin -in-charge: cement: 2 fine sand: 4 gs by Head Load to the 1 gs by Head Load to the 1 gs tacking at a suitable loce and Load to the top of bu g at a suitable location o g at a suitable load to the top l and stacking at a suita by Head Load to the top	class bricks in superstrute (14 (1 Cement : 4 Fine saugle layer including cost) glocamplete. ment : 4 fine sand). ment : 4 fine sand). n walls/ floors including to cation and direction of the saud incation and direction of the saud incation polypropylene Polypropyl	maged bitumen felt from ble location having a lean-charge complete. class bricks in superstrut 4 fine sand 2 complete. ment: 4 fine sand 3 complete. ment: 4 fine sand 5 complete. ment: 4 fine sand 6 cat fine sand 9 complete. ment: 4 fine sand 1 complete. ment: 2 fine sand 1 complete. ment: 2 fine sand 1 complete. ment: 2 fine sand 1 complete. ment: 4 fine sand 1 c
a location complete	suitable location comple le top of building upto a l	to the top of building up	Charges of lifting sand by Head Load to the top of building upto a height of 5.50m abo the ground level and stacking at a suitable location complete. Charges of lifting stone aggregate by Head Load to the top of building upto a height of	Charges of lifting cement bags by Head Load to the top of building upto a height of 5.50m above the ground level and stacking at a suitable location complete. Charges of lifting sand by Head Load to the top of building upto a height of 5.50m above the ground level and stacking at a suitable location complete. Charges of lifting stone aggregate by Head Load to the top of building upto a height of	Providing and laying grading of roof for water proofing treatment complete as required as per direction of the Engineer-in-charge: (i) Cement concrete 1:2:4 (1 cement : 2 fine sand : 4 graded stone aggregate 20 mm nominal size). Charges of lifting cement bags by Head Load to the top of building upto a height of 5.50n above the ground level and stacking at a suitable location complete. Charges of lifting sand by Head Load to the top of building upto a height of 5.50m above the ground level and stacking at a suitable location complete.	Half brick masonry with first class bricks in superstructure above plinth level and upto foor V level: In cement mortar 1:4 (1 Cement: 4 Fine sand). 12 mm cement plaster in single layer including cost of materials required and finishing even and smooth and curing complete. (I) In Cement mortar 1:4 (1 cement: 4 fine sand). Charges of making chases in walls/floors including making good the wall after placing of APP sheet as per the specification and direction of the Engineer-in-charge complete. (I)Size of chases upto 7.5 x 7.5 cm. Providing and laying APP (Atactic Polypropylene Polymer) modified prefabricated five layers are mat consisting of a coat of bitumen primer for bitumen membrane @ 0.40 ltr/sq. mtr. by the same membrane manufacture of density at 25 oC, 0.87 – 0.89 kg/ltr and viscocity 70 – 160 cps. over the primer coat the layer of membrane shall be laid using butane torch and sealing all joints etc. and preparing the surface complete and having overlap of 12%. The vitial physical and chemical parameters of the membrane shall be: Joint strength in longitudinal and transverse direction at 23oC 650/450 N/5 cm. Tear strength in longitudinal and transverse direction at 23oC 650/450 N/5 cm. Tear strength in longitudinal and transverse direction at 23oC 650/450 N/5 cm. Tear strength in longitudinal and transverse direction as 300/250 N. Softening point of membrane not less than 150 oC. Cold flexibility shall be upto -2 oC when tested in accordance with ASTM, D – 5147. The laying of membrane shall be got done through the authorised applicator of the manufacture of membrane as per specification and instruction of the Engineer-in-charge complete. Providing and laying grading of roof for water proofing treatment complete as required as per direction of the Engineer-in-charge complete. Charges of lifting sement bags by Head Load to the top of building upto a height of 5.50m above the ground level and stacking at a suitable location complete.	Charges of removing the damaged bitumen felt from the surface of roof followed by disposal of debris at a suitable location having a lead of 50m as per the direction and instruction of the Engineer-in-charge complete. Half brick masonry with first class bricks in superstructure above plinth level and upto vevel: In cement mortar 1:4 (1 Cement: 4 Fine sand). 12 mm cement plaster in single layer including cost of materials required and finishing even and smooth and curing complete. In Cement mortar 1:4 (1 Cement: 4 Fine sand). Charges of making chases in walls/ floors including making good the wall after placin APP sheet as per the specification and direction of the Engineer-in-charge complete. (i)Size of chases upto 7.5 x 7.5 cm. Providing and laying APP (Atactic Polypropylene Polymen) modified prefabricated five man transverse upto 7.5 x 7.5 cm. Providing and laying of a coat of bitumen prime place for polymen membrane with non-woven polypers ame thick water proofling membrane, black finished reinforced with non-woven polypers amen thick water proofling membrane, black finished reinforced with non-woven polypers amen thick water proofling remains and direction of the Engineer-in-charge complete. (i) Size of chases upto 7.5 x 7.5 cm. Providing and laying of a coat of bitumen prime for bitumen membrane with 2.0 o.0 o.0 o.0 o.0 o.0 o.0 o.0 o.0 o.0 o
	upto a height of plete.		tht of 5.50m above	to a height of 5.50m Jht of 5.50m above	olete as required as gregate 20 mm to a height of 5.50m that of 5.50m above	plinth level and upto foor required and finishing (i) I the wall after placing of in-charge complete. led prefabricated five layer with non-woven polyester he (ii) 0.40 ltr/sq. mtr. by 9 kg/llr and viscocity 70 - d using butane torch and ving an overlap of 12%. all be: Joint strength in first of membrane not less coordance with ASTM, D-horised applicator of the the Engineer-in-charge (i) 3mm thick. complete as required as complete as required as gupto a height of 5.50m above including and provided in the engineer of the strength of the engineer of the gupto a height of 5.50m above	oof followed by he direction and he direction and who foor ired and finishing (i) wall after placing of harge complete. Wall after placing of harge complete. Wall after placing of harge complete. Wall after placing of 10,40 ltr/sq, mtr. by
,	Cum	Cum		n Bags		, e ;	
	0.72	1.03	70.47	}	0.82		178 0.0 82 282 282
		-					
						φ	
					To the state of th		
					1		
-		1	}				

Z Z

Total = Say Rs